

JEHIER

Saint Lezin road
P.O. BOX 29
49120 CHEMILLE
France

Tél. : (33) (0)2.41.64.54.00
Fax : (33) (0)2.41.64.54.01

KB 44

DESCRIPTION	:	<i>The « KB 44 » adhesive tape is made of a reinforced elastomer fabric coated on its back with a permanent adhesive, protected by a siliconed paper</i>
THICKNESS	:	<i>0.4 mm (0.016")</i>
WEIGHT PER M2	:	<i>Without protecting paper : 250 g ± 10 % (7.4 oz/yd2)</i>
PEELING ADHESIVENESS	:	<i>10 N/25 mm on aluminium sheet (V=100 mm/min)</i>
WORKING TEMPERATURE	:	<i>- 50 °C to + 90 °C (-60 °F to 195 °F)</i>
FIRE RESISTANCE :	:	<i>This material meets :</i> <ul style="list-style-type: none"><i>• FAR 25 par. 853 if tested according to the vertical Bunsenburner test, applied on an aluminium 25 ± 5 µm</i><i>• Radiant panel test requirements according to FAR 25.856 (a) when tested applied on ABS5049B,</i> <i>Other configurations to be tested</i>
CONDITIONING	:	<i>Roll of 50 meters long.</i> <i>Width : 30, 50, 75 and 100 mm (1.2", 2" ; 3", 4")</i> <i>(Please contact us for different sizes)</i>

Ed. 09/2006
Page 1 sur 2

JEHIER

Saint Lezin road
P.O. BOX 29
49120 CHEMILLE
France

Tél. : (33) (0)2.41.64.54.00
Fax : (33) (0)2.41.64.54.01

KB 44

COLOURS	:	71 : brown 12 : grey (others colours on request)
REFERENCE	:	KB44/Colour/Width in mm
APPLICATIONS	:	Implemented with polyimide foams 353R and 355 R for Air-ducting Insulation.
DIRECTION FOR USE	:	Clean the area onto which the adhesive tape must be fitted. Peel off the protecting paper Fit the tape and press with hand.
APPLICABLE SPECIFICATIONS	:	Airbus : ABS5662C
SHELF LIFE	:	Shelf life : - 24 months from manufacturing date. Guaranteed rest shelf life : - Minimum 12 months from delivery date.
STORAGE CONDITIONS	:	Maximum 30 °C at 50 % relative humidity.

Ed. 09/2006
Page 2 sur 2